Round Camirror | Camera in Mirror with Remote Control and On Screen Display

ITEM NUMBER: CAM-MIR


FEATURES


- 540TVL
- 1/3" Sony Super HAD Color CCD Sensor
- Lens: 4.3mm lens
- Working Voltage Range: DC12~18V
- Built-in OSD menu with a wireless remote control.

SPECIFICATION:

Model No.	CAM-MIR
CMRL5	OSD
Built-In Lens	4.3mm
Lens Angle	78°
Color CCD	1/3" Sony Super HAD Color CCD Sensor
System	NTSC / PAL
SYNC System	Internal
Number of Pixel	NTSC:768(H)x494(V)
Resolution	540 TV Lines
Minimum Illumination	0.1 Lux
S / N Ratio	More than 50 dB
Electronic Shutter	1/60 (50) to 1 / 100,000 sec.
Gamma Correction	0.45
White Balance	Auto (ATW) 2300-9800° K
AGC	Automatic
BLC	Automatic (64 area set up by OSD)
Current Consumption	100 mA
Working Voltage	DC 12~18V
Video Output	1.0 Vp-p Composite, 75Ω
Video Output Dual Port	Optional
OSD Function	Optional
Operation Temperature	14~140°F (-10°~ 60°C)
Operation Humidity	0 ~ 95% RH
Dimension	17.32" (440mm)









OSD Menu:

Lens, Shutter, BLC, AGC, White Balance, Mirror, Adjust (Contrast, Sharpness, CB Gain, CR Gain), Function (Reset, Day Night, Motion, Privacy, Gamma), Language (English, Japanese, Chinese, Chinese Simplified, Korean), and Camera ID.